


COMPOSITE BRIDGE PLUG



DESCRIPTION

The WYOMING COMPLETION TECHNOLOGIES 10K Composite Bridge Plug provides a cost-effective alternative to temporarily isolate multiple zones for fracturing, or other treatments. The composite material allows for quicker drill times and less formation damage. Interlocking tapers on the top and bottom prevent plug remnants from rotating while removing multiple plugs.

FEATURES/BENEFITS

- Cost effective & dependable
- Nitrile elastomer element system
- One piece, full circle slips
- Quick and easy drill-up
- Inter-locking taper on both top and bottom
- Tested at 350° F and 10,000 psi

APPLICATIONS

- Temporary zone isolation
- Temporary plug

TECHNICAL DATA

PRODUCT #	CASING				TOOL
	OD	ID MAX.	ID MIN.	Weight	OD
	Inches mm	Inches mm	Inches mm	Lb/Ft Kg/m	Inches mm
43CCBP	4-1/2	4.09	3.92	9.5 – 13.5	3.61
	114.3	103.88	99.5	14.1 – 20.1	91.7
45CCBP	5-1/2	5.04	4.55	13 – 23	4.31
	139.7	128.12	115.44	19.5 – 34.2	109.5
45CCBPB	5-1/2	5.04	4.65	13 – 20	4.50
	139.7	128.12	18.19	19.5 – 29.8	114.3

WYOMING COMPLETION TECHNOLOGIES, INC.

1110 ROAD 9 PO BOX 46
POWELL, WYOMING 82435
PHONE: (307) 754-5429 FAX: (307) 754-5927
HECHTS@DIRECTAIRNET.COM